

High temperature and  
Long life grease

# MULTEMP ET - K

MULTEMP ET-K is designed especially for use in rolling bearings of automobile electrical equipment such as alternators and electromagnetic clutches. MULTEMP ET-K has long performance life under high temperature and high speed conditions, together with excellent rust preventive properties.

## Typical analyses

Usage temperature range	- 40	200
-------------------------	------	-----

Test item		Test method	MULTEMP ET - K
Thickener			aromatic diurea
Base oil			ether - based synthetic oil + polyolester
Base oil kinematic viscosity (40 ) mm <sup>2</sup> /s		ASTM D 445	95.1
Appearance			light brown, buttery
Worked penetration		ASTM D 217	300
Dropping point		ASTM D 566	230
Oil separation mass%	100 ,24h	ASTM D 6184 Mod.	1.0
	150 ,24h		1.6
Low - temperature torque mN·m	( - 30 )	ASTM D 1478 - 63	330
	Starting torque Running torque		96
Corrosion preventive properties (52 ,48h)		ASTM D 1743 - 73	# 1

08/5

**KYODO YUSHI Co., LTD.**

2 - 2 - 30 , Tsujido Kandai, Fujiswa-Shi, Kanagawa 251-8588, Japan  
Phone: (0466) 33 - 3157 Facsimile: (0466) 33 - 3054